

# POOL & SPA PRODUCT PORTFOLIO



Residential



Apartment  
Buildings



Schools, Colleges,  
& Universities



Hotels  
& Restaurants



Non-Profit  
Organizations



Pool & Spa

# RESIDENTIAL POOL & SPA HEATERS



## AVIA®

264 MBTUH - 399 MBTUH  
84% Efficiency

Featuring ProTek Shield™,  
Raymote® connectivity, Low  
NO<sub>x</sub> design.



## AVIA® with NiTek

264 MBTUH - 399 MBTUH  
84% Efficiency

Featuring ProTek Shield™,  
Raymote® connectivity, Low  
NO<sub>x</sub> design, NiTek™ Heat  
Exchanger Technology.



## Digital

199 MBTUH - 399 MBTUH  
82% Efficiency

Featuring ProTek Shield™,  
also available as Millivolt,  
Cupronickel.



## Above Ground

105 MBTUH & 150 MBTUH  
82% Efficiency

Analog (106 Model) or Digital  
Control (156 Model).



## Crosswind®

28 MBTUH - 61 MBTUH  
5.8 ~ 5.7 C.O.P. (80,80,80)<sup>1</sup>

27 MBTUH - 58 MBTUH  
5.6 ~ 5.3 C.O.P. (80,63,80)<sup>1</sup>



## Crosswind® V

85 MBTUH - 138 MBTUH  
5.8 ~ 6.0 C.O.P. (80,80,80)<sup>1</sup>

80 MBTUH - 130 MBTUH  
5.5 ~ 5.8 C.O.P. (80,63,80)<sup>1</sup>



## Classic & Compact Series

48 MBTUH - 140 MBTUH  
5.7 ~ 5.6 C.O.P. (80,80,80)<sup>1</sup>

46 MBTUH - 130 MBTUH  
5.5 ~ 5.3 C.O.P. (80,63,80)<sup>1</sup>



## E3T®

19 MBTUH - 92 MBTUH  
5.5 - 27 kW

 Raymote Equipped

 Gas  Electric  Heat Pump

# PROFESSIONAL POOL & SPA HEATERS



## Digital ASME 🔥

199 MBTUH - 399 MBTUH  
82% Efficiency

*Featuring ProTek Shield™,  
also available as Low NO<sub>x</sub>,  
Cupronickel.*



## Professional 🔥

266 MBTUH - 399 MBTUH

*Featuring ProTek Shield™.*



## Professional X94 🔥

399 MBTUH  
94% Efficiency



## Professional Heat Pump 🌬️

140 MBTUH - 170 MBTUH  
6.1 ~ 5.8 C.O.P. (80,80,80)1

133 MBTUH - 155 MBTUH  
5.8 ~ 5.3 C.O.P. (80,63,80)1



# PROFESSIONAL POOL & SPA HEATERS



## XTherm® Indirect

1 MMBTUH - 2 MMBTUH  
Up to 96% Efficiency

*Cupronickel indirect heat exchanger standard. Titanium indirect heat exchanger and warranty upgrade option. Cascades up to 8 units.*



## XTherm®

1 MMBTUH - 4 MMBTUH  
97% Efficiency

*Hybrid: cupronickel finned water-tube heat exchanger with secondary stainless steel condensing water-tube heat exchanger. Cascades up to 8 units.*



## MVB®

500 MBTUH - 2 MMBTUH  
83-83.3% Efficiency

*Cascades up to 8 units.*



## Hi Delta®

500 MBTUH - 2.3 MMBTUH  
83.1% Efficiency

*Cascades up to 8 units. SureRack® vertical racking option.*



## E3T® 3-Phase

61 MMBTUH - 184 MMBTUH  
18 - 54kW

80-character display. Durable against salt pool water conditions, standard on all models. Includes Flow Protection, Low-Temp Operating Mode, Load Detection, and 50/50 Mode<sup>2</sup>.



Scan here to visit the Raypak Pool Products page

Residential | Professional | Protégé

 Raymote Equipped

 Gas  Electric  Heat Pump

<sup>1</sup> Tested to AHRI 1160

<sup>2</sup> Available on models with 6 heating elements.

**Raypak®**  
A Rheem® Company

Learn more at [raypak.com](http://raypak.com)

2151 Eastman Avenue | Oxnard, CA 93030 | 805-278-5300

©2023 Raypak, Inc. RP-P-900-6 Rev B Effective 11-6-23 Replaces 03-01-23