

# CRISTAL-FLO™ II

## SAND FILTER

Press, twist and relax.

Easy maintenance and outstanding water quality have made the Sta-Rite® Cristal-Flo II Sand Filter the top choice among pool professionals and pool owners alike. Through innovative engineering, the filter's dirt-handling capacity is maximized, which extends the time between cleanings (backwashing). This innovation takes sand filtration technology to the next level by delivering superior quality, performance and value at an affordable price.



[PENTAIR.COM](http://PENTAIR.COM)



## CRISTAL-FLO™ II SAND FILTER

### For all the right reasons

Convenience, low maintenance and water quality are the reasons for sand's popularity. The Cristal-Flo II filter is a time-tested favorite with pool owners due to its extended maintenance cycles, easy-to-operate control valve selector and outstanding water clarity. The biggest reason for installing a Cristal-Flo II filter: the additional leisure time you'll spend enjoying your pool.



#### KEY FEATURES

##### Top-mount, 6-function, 1-1/2" multi-port valve

Features a pressure gauge and manual air relief for optimum filtration efficiency.

##### One-piece thermoplastic tank

For strength and corrosion resistance.

##### Internal Design

Ensures that water is exposed to the maximum sand surface area for superior filtration performance and efficient backwashing.

##### Combination water and sand drain

For easy service and winterizing.

Model Number	For Pools up to 8 Hour Turnover (gal.)	Filter Area (Sq. Ft.)	Flow Rate GPM <sup>1</sup>	Valve	Sand Required (lbs.)
CF1115	16,800	1.2	35	1½" Multi-Port	100
CF1119	19,200	1.9	40	1½" Multi-Port	150
CF1122	28,800	2.6	60	1½" Multi-Port	250
CF1124	33,600	3.2	70	1½" Multi-Port	300
CF1126*	36,000	3.9	75	2" Multi-Port	350

<sup>1</sup>Use only #20 white quartz silica sand, size range .40-.55 mm; 12" to 15" sand bed depth required.

Operating Limits - Maximum continual operating pressure is 50 PSI for 24" and 26" tanks, 35 PSI for 20" and smaller. Maximum operating water temperature (internal filter) is 95°F (35°C).

\*CF1126 available with 1½" or 2" valve.



1620 Hawkins Ave | Sanford, NC 27330 | United States | 800.831.7133 | [staritepool.com](http://staritepool.com)

All indicated Pentair trademarks and logos are property of Pentair Inc. or its global affiliates in the U.S.A. and/or other countries. Third party registered and unregistered trademarks and logos are the property of their respective owners.

P1-095 2/20 ©2020 Pentair. All Rights Reserved

#### TRADEGRADE

The TradeGrade family of products is exclusively made for and sold by the world's most demanding pool professionals.